

VKA Event Guidelines (Effective January 1, 2017)

Revised 11/15/16



The Vintage Karting Association

A Nevada Corporation

These Vintage Karting Association (VKA) Guidelines are for vintage karts manufactured in the years 1956 through 1987. The VKA promotes vintage kart exhibitions in two ways; Static Display for judging with emphasis on originality and workmanship with period correct details, and Active Demonstrations where the karts operate on a track in a safety minded manner. These VKA Guidelines are written for the participant, sponsor, and promoter so events can be organized in a similar manner across the country with safety as the priority issue. Although these Guidelines are intended to promote safety and consistency between events across the country, implementation is the sole responsibility of the promoter and the track owner. VKA is not liable for implementation of these Guidelines.

A. Safety

Safety is the most important aspect of any motor sport and is paramount in the exhibition/demonstration of vintage karts. Safety is addressed in the relevant portions of this document. Safety should be highlighted at each event.

- The track owner/promoter should have a signed liability waiver by the participant for each event.
- Safety issues must be discussed at the drivers' meeting.
- All participants are required to attend the drivers' meeting.
- The owner/promoter may refuse to allow a driver to participate based on the driver's past kart driving record, the driver's physical condition or advice from track medical personnel or from a hospital or other medical facility.
- An ambulance with trained medical personnel **should** be present at all VKA demonstration events including all practice sessions or trained medical personnel should be readily available.
- **Effective 2017, only 2010 and later Snell** approved helmets should be used for VKA karting events. Helmets should be presented at registration for the event for inspection.

B. Planning and Preparation

For each VKA event, a VKA representative should be recognized as the focal point for coordination and promotion. The responsibilities of that person include:

- Publishes information for the event.
- Acts as liaison between the event and VKA.
- Supports the establishment of a panel for judging and/or collects voting information for kart show awards.
- Promotes the need for a person to report on the event for publication in the VKA Newsletter and Website.

Changes are highlighted in yellow.

C. Demonstrations Events

The organization and rules of the event and grouping of VKA classes are the prerogative of the track owner/operator. The VKA encourages the adoption of these *Guidelines* for safety and uniformity to all vintage karting events across the country. The VKA seeks to recreate the look and feel of actual karting events of the 50's, 60's, 70's & 80's and perform for the enjoyment of spectators and participants. Actual operation of vintage karts on the track provides the greatest spectator appeal and photographic opportunities needed to promote vintage karting. Providing a fun and exciting opportunity to drive these machines. The demonstrations in two different levels will encourage more people to join the sport. Tier I demonstrations will be "flagged" demonstrations, with scoring and awards (see Paragraph 11). Tier II demonstrations will be "non-flagged" demonstrations with no scoring and no awards (see Paragraph 12, below). Maintaining operational karts will allow "karting veterans" to once again use their special driving and mechanical talents and to pass them on to those new to vintage era karts.

1. Drivers

- a. All drivers must attend the drivers' meeting to be eligible to participate in the event.
- b. Juniors: 10 years minimum and under age 15 should run in the Junior Class with a single engine. Additional safety briefing and compliance is recommended for this class.
- c. Drivers 15 years of age or older are permitted to operate any type of single engine vintage kart. There is no maximum age.
- d. Drivers of dual engine karts should be 18-years minimum age.
- e. All first-time drivers, novice and juniors in a VKA event should demonstrate their driving ability to the satisfaction of the track owner/operator at the event in order to participate. They should also start all Heats in rear of the grid. This should apply to the first three events that the driver competes in. They should display an "X" on the back of their helmet.
- f. No alcohol, illegal drugs, or legal drugs that would impair driving ability should be allowed.
- g. All drivers must demonstrate proficiency and control of a kart on the track.
- h. Drivers who weigh 190 pounds or more at Registration, may be place in a "vintage weight" class as a Promoter's Option.

2. Driving Rules

The Host Track should explain the driving rules at their track during the Drivers' Meeting. It is the right and responsibility of the Host Track to determine the rules and procedures of the vintage karting event to ensure a safe event. Additionally, VKA encourages them to adopt this entire package of guidelines to provide uniformity to all vintage karting events across the country.

- a. Contact between karts and overly aggressive or reckless driving will not be tolerated. Rules and acceptable conduct on the track and in the pits should be conveyed at the drivers' meeting prior to group participation. Safety is paramount. Clean passes, no contact, no strafing, no cutting off and no "Texas starts" before the green flag.
- b. Drivers must attend drivers' meeting with special emphasis on safety. They should be briefed and the Starter/Flagmen should advise them regarding pace lap speeds and techniques. Discuss direct drive starting procedures and the presence of a driver when starting the engine.

Changes are highlighted in yellow.

- c. These words, or something that conveys the expectations of the track owner/operator and the promoter regarding drivers' responsibilities, should be read at the Drivers' Meeting: *"When two karts are entering a turn together the kart that is behind, whether it be an inch or several feet, is required to negotiate the turn without endangering or impairing the progress of the kart in front. Conversely, the kart in front should not take a deliberate line of the course for the reasons of crowding a following competitor off the course."*¹
- d. Drivers who make contact with another karter at anytime during the practice or demonstration Heats should determine if their kart is safe to continue. If not, they should stop or return to the pits immediately, depending on the extent of the damage. After returning to the pits, both drivers should seek each other out and discuss the bumping incident and try to resolve and correct why incident happened.
- e. Drivers with questionable kart driving record may be denied registration by the track owner/operator or promoter.

3. Official Entrant/Entry

The driver is the official entrant for an event when properly documented by the track owner/operator and having participated in the drivers' meeting. The driver (entrant) may enter more than one kart (entry) at an event. Entered karts should be classified according to Vintage Class Structure (see para. 6).

4. Personal Protective Equipment Promoters Will Require:

- a. Snell approved full-face helmet with face shield. In 2017, only 2010 and later Snell approved helmets should be used for VKA karting events. Helmets should be presented at registration for the event for inspection Vintage Helmets are not allowed.
- b. Helmet support (Neck Collar) – Preferably the new Leatt[®]-Type.
- c. Leather, Vinyl, Cordura[®], or abrasion resistant nylon jacket. Driving suits, Nomex[®] undergarments and earplugs are permitted and are strongly recommended due to possible damage to hearing.
- d. Full-finger protection gloves, leather or nylon.
- e. Long pants of a durable material.
- f. Shoes or boots.
- g. Hair protruding more than 4" from the helmet must be secured under the helmet.
- h. Juniors must wear approved rib protectors.

5. Kart Equipment

No official tech teardown inspection should occur at VKA events. "Self-Policing" may occur among class entrants. Violating the equipment guidelines for the purpose of performance gain is inappropriate behavior. Those engaging in such behavior are not welcome at VKA events.

- a. All karts (except reproductions) should be initially available during the class era.
- b. Karts can be an original production kart from the Historic Era (1964 and before), a continuation kart (identical to the original model, but produced after the Historic Era), a reproduction of a Historic Era production kart, or a homebuilt design actually produced

¹ 1968 IKF Rule Book; Race Rule #19

Changes are highlighted in yellow.

during the vintage era.

- c. Every effort should be made to use appropriate equipment from the kart's proper era. Documentation of questionable items is encouraged. If a similar part or accessory did not exist during the Vintage Kart Era, then it doesn't belong on the kart now (approved safety issues being the exception).
- d. Authentic variations may be authorized at the race official's discretion.
- e. Seat belts should not be allowed in any open frame karts, but are required in FKE types.
- f. Modifications that increase performance or handling that change characteristics of era designed karts should not be permitted.
- g. No bodywork should be permitted except number panels (not applicable to FKE karts).
- h. **Tires:**
 - Rear Engine Karts – See Tire Schedule (Para. 6b, below)
 - Sidewinders – See Tire Schedule (Para. 6b, below)
- i. **Engines:**
 - Should have been initially produced in the class era.
 - Engines can be stock or modified. Period correct modifications are permitted. Unlimited over boring is allowed for the purpose of extending engine life. Original stroke should be maintained with exception of engines in the historical era (1956-1961).
 - If the engine or accessory was used in the era of the kart, then it can be used at a VKA event.
 - See detail of approved engines. (Para. 6c, below)
- j. **Exhaust:**
 - Box-type mufflers or tuned expansion chambers (no slipper types).
 - Some events may require a form of muffler to participate due to local noise restrictions.
 - Open headers permitted at the discretion of the Promoter. There will be situations in the Historic class that require the use of open headers.
- k. **Clutch and Chain:**
 - All karts participating in VKA demonstration events should use #35 or #40 chain.
 - Clutches are not required.
 - If clutches are used, they should be of the type used prior to 1987, except:
 1. Wet clutch used prior to 1985 are permitted on any kart except Sportsman, Historic Class, Mac49/Saw, Junior/Women and Sportsman S/W Stock Appearing.
 2. No DXL or disc type clutches permitted on Rear Engine Karts.
 3. No Axle Clutches permitted.

Changes are highlighted in yellow.

4. Common clutches allowed at VKA events are Max Torque, Rev Grip, Comet, L & T wet disc, Horstman DXL, Burco, Hartman, Noram and other vintage style clutches. No modern style clutches allowed.
 - A third bearing support or guard to contain the clutch in the event of crankshaft breakage should be on all Rear and Sidewinder karts using an oil bath outboard mounted clutch (toward the outside of the chassis). Construction of clutch guards must be of a material equal to or greater in strength than .090" aluminum.
- l. **Weight**
 - There are no minimum or maximum weight limits although drivers who weigh 190 pounds or more at Registration, may be place in a "vintage weight" class as a Promoter's Option.
 - Any weights or ballast must be securely fastened.
- m. **Fuel:** Gasoline/oil or Methanol/oil. No power inducing additives such as oxygenated fuels, hydrazine, nitro, nitrous oxide, or propylene oxide, *etc.* should be used.
- n. **Brakes:** Modern brake upgrades are permitted and recommended. When using a modern caliper it is recommend that a modern-type disc is used for compatibility. Scrub brakes should not be used in racing events, except on Historic Class machines if they were original equipment. The use of modern European Braking systems is not in the spirit of Vintage Karting; MCP, Ripley and Airheart Brakes are consistent with historical preservation and are readily available.
- o. **Axles:** When using modern type axles which require wheel hubs, it is recommended that rear axles have a locking collar next to the wheel hub and two collars on the dual karts. It is imperative to keep the rear wheel hubs from moving inwards.
- p. **Original wheels** are recommended, otherwise any two-part or modern single-piece wheel is acceptable. Wheel and tire width should be consistent with original equipment. Example: Rear engine dual karts had a maximum tire width of 6 inches.
- q. **Seats:** Must be maintained in their original design. Creating additional side panels to hold the driver in a rear engine kart is not acceptable. Sidewinders may use equivalent modern seats.



Changes are highlighted in yellow.

6. VKA Event Class Guidelines - VINTAGE CLASS STRUCTURE²

1. HISTORIC	1956 to 1964 rear engine karts and engines; single, dual, or triple engines, 16.5 c.i. (270cc) max displacement; Must have vintage-style dry clutches or direct drive ; box muffler; vintage tire required; Promoter may split class as per VKA Guidelines (Para. 6a, below); duals/triples in front. This is a non-points, demonstration class.
2. JUNIOR/WOMEN REAR OR SIDEWINDER	Junior (Boys/Girls ages 10-14) - Single 100cc (6.1 c.u. in.) max. American Fan Cooled Engine (<i>i.e.</i> West Bend, McCulloch, Power Products, Homelite) or West Bend 820. All engines will run single HL 1” or smaller throttle bore Any intake allowed, but West Bend must use V-Reed or Go Power, 4 or 6 pedal cage, Vintage style dry clutch, box muffler and vintage tires required. Yamaha KT100 engine may be used with WA55 Walbro carb, dry clutch, “limited” exhaust system and vintage tires. (See Yamaha Limited Class for pipe requirements.) (Junior and Women class can run rear or sidewinder kart.)
3. SPORTSMAN REAR	Rear American engines; 8.2 c.i. (135cc) max displacement; WB-820 with 8.2 c.i. (135cc) max displacement must be industrial-type; McCullochs must be 6.1 c.i. (100cc) max displacement or saw blocks over 80cc. small single intake manifold allowed (WB V-reed, Homelite reed, Go Power reed, etc.). Manifold to have an HL bolt pattern. Single HL 1 inch maximum throttle bore carburetor Small Mac flat-back carb OK. Must have vintage-style dry clutch, box muffler and vintage tires. No MC-91, 92, or 93 engines.
4. MAC 49/SAW	Rear engine karts; Mc49 or 80cc saw block engines. 1.375 maximum stroke; Aftermarket small single intake manifolds allowed (WB V-reed, Homelite reed, Go Power reed, etc.) or factory Mc 49 intake. Manifold to have an HL bolt pattern. Single HL 1 inch maximum throttle bore carburetor or small Mac flat-back carburetor; Vintage style dry clutch; Box muffler; Vintage tires.
5. SINGLE REAR 6.1	Rear engine karts; American or Foreign engines, 6.1 c.i. (100cc) max displacement; pipes and oil clutches allowed; no disc clutches; any carburetor combinations, vintage tires.
6. SINGLE REAR 8.2	Rear engine karts; American or Foreign engines, 8.2 c.i. (135cc) max displacement; pipes and oil clutches allowed; no disc clutches; any carburetor combinations, vintage tires.
7. DUAL REAR, B- & C-OPEN	C-Open: American or Foreign engines, 16.5 c.i. (270cc) max displacement; pipes and oil clutches (no disc clutches); vintage tires. Any Historic B or C Class dual engine rear karts may run this class. B-Open: American or Foreign engines, 12.2 c.i. (200 cc) max, dry clutch, box mufflers, #35 chain, and vintage tires. (B-Open to be run in concert with C-Open and scored separately.)
8. SINGLE 6.1 S/W AMER.	Pre-1980 sidewinder with American fan cooled engines, 6.1 c.i. (100cc) max displacement; engine clutches only; pipes allowed; modern tires allowed; one inch axle. Max kart width of 48 inches.
9. SINGLE 8.2 S/W AMER.	Pre-1980 sidewinder with American fan cooled engines, 8.2 c.i. (135cc) max displacement; engine clutches only; pipes allowed; modern tires allowed; one inch axle. Max kart width of 48 inches.
10. SINGLE 6.1 S/W FOREIGN	Pre-1980 sidewinder with Foreign or American engines, 6.1 c.i. (100cc) max displacement produced before 1980; engine clutches only; pipes allowed; modern tires allowed; one inch axle. Max kart width of 48 inches.
11. SINGLE 8.2 S/W FOREIGN	Pre-1980 sidewinder with Foreign or American engines, 8.2 c.i. (100cc) max displacement produced before 1980; engine clutches only; pipes allowed; modern tires allowed; one inch axle. Max kart width of 48 inches.
12. OVER-60	Drivers 60yrs +; Rear or pre-1980 sidewinder karts; American, fan-cooled , 6.1 c.i. (100cc) max displacement engines; pipes allowed; oil clutches allowed; no disc clutches; vintage tires; any carburetor combinations. Promoters should consider separating the sidewinder and rear engine karts for scoring purposes when participation is sufficient to do so. Allow sidewinders to start in the front. Max kart width of 48 inches.
13. DUAL SIDEWINDER	Sidewinder with Foreign or American engines, 16.5 c.i. (270cc) max displacement; engine clutches only; pipes allowed; modern tires allowed. Tire compound durometer minimum of 48. Bridgestone YLC and MG tires allowed. May use any approved single sidewinder tire (see par. 6b, below); 1¼” axle allowed if original; karts and engines must be manufactured prior to ‘83.
14. 80-87 SIDEWINDER	1980 – 1987 sidewinder with Foreign or American engines, 6.1 c.i. (100cc) max displacement; pipes allowed; engine clutches only; modern tires allowed; 1¼” axle allowed; kart and engine must be manufactured prior to 1988 – see Engine Schedule. (Para. 6c, below) Max kart width of 50 inches.
15. SPORTSMAN S/W (STOCK APPEARING)	Sidewinder (pre-1980) with 6.1 c.i. (100cc) max displacement, American fan cooled engine; single carburetor (Mikuni, Tillotson, or McCulloch), any size throttle bore; Factory V4 intake; modern tires; box muffler; vintage-style dry clutch (Horstman Rev Grip or Max-Torque). West Bend-Only Class- Stock appearing West Bend 820 with stock bore and stroke (fan cooled), box muffler, small, single West Bend factory manifold and V4 reed cage with a 1: max throttle bore, HL carb, modern style tires, pre-1980 sidewinder with 1” axle, OEM Max-Torque dry clutch with no add-ons. To be run in concert with Sportsman S/W, but scored separately. For drivers 15 years or older. Max kart width of 48 inches.

² Drivers who weigh 190 pounds or more at Registration, may be place in a “vintage weight” sub-class as a Promoter’s Option.

Changes are highlighted in yellow.

16. YAMAHA PISTON PORT	Sidewinder karts (thru 1987) with single 100cc (KT100S), 1975 to present; piston port only; max. bore - 2.090"; max. stroke - 1.816"; "stock appearing" - internal modifications allowed ; factory ignition system only (exception- "RVL" TCI replacement module OK); Walbro WB3A carburetor only; pipe allowed; Horstman DXL wet disc, Hartman, L & T wet disc, Burco, Max Torque clutches only (no modern clutches); Third bearing support required; 1" or 1¼" axle; modern tires; gasoline only. Max kart width of 50 inches.
17. YAMAHA LIMITED	Sidewinder karts (thru 1987) with single KT100s, piston-port engine, max bore – 2.090" – max stroke = 1.816" – WKA stock specification guidelines to apply; factory ignition systems only (exception- RLV TCI replacement module allowed); Walbro WB3A carb with max 0.950" venturi; "limited" pipe (FY-Sr/K1/K2) at 12" minimum length (piston to start of first cone); Horstman DXL, Hartman, L+T, Burco, Max-Torque clutches only; no modern clutches; no direct drive or Tomar clutches; 3 rd bearing support required; Max kart width of 50 inches.
OPTIONAL CLASS	Straight Axle Sidewinder
ENGINES	Period Correct 100cc max; Foreign motors to have single carburetor as manufactured, and must be produced prior to 1975. (See paragraph 6c.iv for allowable foreign engines.)
TIRES	Vintage-style tires (square corners); 6" Max width per durometer guidelines
CLUTCHES	Period correct clutches (e.g., Rev Grip, Horstman, Burco, Hartman, Max-Torque. NO DISC CLUTCHES
EXHAUST:	Any can, period correct pipe, or box muffler
REAR AXLE	1" only, unless manufactured with 1¼" from the factory
FUEL	Gas or alcohol
WEIGHT	No weight restrictions
TECH	No tech

(The **Junior/Women Class** was created for the benefit of novice drivers to come into Vintage Karting at a lower budget level, and to use this class to improve their skills in order to progress to other desired classes. Women of any age over **10** may run in this class.)

6a. VKA class guidelines

Kart Manufactured between 1956 and **1987** are eligible for participation.

Open Headers and Silencers	At the discretion of the Promoter.
Classes 1-12	Require a 1 inch axle. Karts and Engines must be from 1956 to 1979 era.
Vintage tires –	65 durometer min refer to VKA Acceptable Vintage Tire schedule.
Modern tires -	Dual S/W – 48 durometer minimum; Single S/W – 56 durometer minimum. Refer to VKA Acceptable Modern Tire Schedule (Para. 6b.)
Modifications	Allowed with vintage period type components.
Direct Drive	Allowed in all classes.
Kart Chassis	To remain in their original design from their model year. Brake upgrades allowed. Reproduction and Specials allowed, but should be vintage-type.

Dual S/W- 48 durometer minimum: Single S/W- 56 durometer minimum. Refer to acceptable modern tire schedule.

Historic Classes: The Promoter at his discretion, depending on turn out at the event may separate the historic classes into two groups:

1956-1961 Era

- MC-1, MC-5, MC-6, MC-10, MC-20, West Bend 510, 580, 700
- Power Products AH58, super AH58
- Homelite K-82 to K-100
- Clinton A400, A490, A500, E-65

To include any other engines accepted by the National Karting associations in the period.

Changes are highlighted in yellow.

Vintage Speed 4.10/3.50-4: 11x3.50-5: 11x4.50-5: 11x6.00-5

Kenda 4.10x3.50-4: 4.10x3.50-5: 4.10x3.50-6

These current production tires should have a minimum tire durometer of 65 @ 70 deg. temperature. The committee may add or delete from the above list as needed for the continued enjoyment and stability of vintage karting.

The following Vintage tires are also acceptable but are no longer being manufactured:

Tex Con Tires	General Tires	Firestone Tires	Continental Tires
Eliminator Tires	Good year Tires	Major Tires	A-1 tires

The VKA does not recommend the use of the above vintage tires for racing events, as many of them may be over 30 years of age. These tires are mostly used for show karts.

Acceptable Tires for Sidewinder Karts at VKA Events

Due to the limited availability of original construction tires, use of modern kart tires of 56 durometer and greater are acceptable. Bridgestone, YHC, YKC, Dunlop SL1, SL-3 & SL-4 and Burris MG-HZ Red; Hoosier R-60A, MoJo D1, Dunlop DDM and Evinco Blue are acceptable.

Exception: Where sidewinders are combined with rear engine karts in classes 2 and 12 – those classes require the use of Vintage style tires.

6c. Engine Guidelines

i. Engine Guidelines for kart classes from 1956 through 1979:

- | | |
|--------------------------|-------------------------|
| *All Clinton | |
| *All McCulloch | *All West Bend/Chrysler |
| Yamaha KT-100A and KT100 | *All Homelite |
| *All Power Products | Standun |
| Maico | Saetta |
| *Poulan S-200 | *Partner R-10 |
| Villiers Pre 1962 | Excelsior Pre 1962 |
| Zundapp Pre 1962 | Komet K-88, K-78 |
| Komet K-55GHR | Komet K-77 |
| Koenig | KT100S |
| Komet K-88TT | LMR 100 |
| Parilla SS-21 | Parilla TT-22, 23 |
| BM-SS96 | BM-SS100 |
| BM-104 | BM-130 |
| Komet K-99, K299 | Dap 100cc |

Changes are highlighted in yellow.

Atlas II
Manx 100S

Hewland Arrow
Corsair T-80&T-81

(Any other engines used during the time-period may also be used.)

*American Fan cooled Engines

ii. Engine guidelines for 1980-1987 Class: 6.1 cubic inch (100cc)

Any of the Pre 1980 Motors:

Atlas II	TKM BT82	Parilla SS22
Corsair T72	TKM RL66	Parilla TT25
Corsair T80	TKM RS98	Parilla TT27
Corsair T80RV/81	TKM S-89	PCR 50/50
Corsair T91	Parilla SS20	PCR 100cc PP
Hewland Arrow	Parilla SS22	Rotax 100
Komet K-80TT		

Any other engines approved by IKF or WKA from 1980-1985

iii. Promoter's option class for 1980-87 Class for 8.2 cubic inch engines

All the above to include the following:

- Komet K-30
- Komet K-35
- DAP Corsair T-60
- DAP Corsair T-62
- TKM-135

iv. Allowable foreign engines for Straight Axle Sidewinder Class

KOMET	BM	DAP
77 88 88tt	100 104	T70 T71
78 78tt	96 (ss) 96/3 tt	T80 T81
PARILLA	SAETTA	
BA13 TG14	V18	
GP15 SS20		
TT22		

7. Exhibition Grouping

In an effort to make demonstrations as realistic as possible while providing the greater safety of similar performance, karts should be grouped as best as practicable. Considerable attention should be given to the different handling capabilities of the various classes especially sidewinder vs. hard tire rear engine karts. Grouping of classes should be at the discretion of the track owner/operator.

Changes are highlighted in yellow.

8. Pre-Tech Preparation

All drivers and participants should check to ensure they have the proper safety equipment needed for the event. The equipment must be sufficient for the level of participation which includes pit crew duties.

- Gloves
- Helmet – must conform to Current Snell Standards
- Helmet collar
- Pants
- Gloves
- Eye protection
- Readily accessible fire extinguisher

9. Safety Technical Inspection

All karts must pass a safety tech inspection before being permitted onto the track. The determination of the inspector on questionable items will be final. The following are items for compliance to participate in demonstration events:

- a. **Suitability for competition:** The basic design of the kart should be suitable for the level of performance in its class while providing the level of safety that was available during its appropriate era. A kart should be considered legal if it remains as it was manufactured.
- b. **Appearance:** The kart should be neat, clean and provide a professional appearance.
- c. **Kart Number:** Karts should be prominently display a 3” (minimum) number on a panel, driver, or helmet for track official or spectator reference.
- d. **Tires:** In good condition and appropriate for the era of the kart.
- e. **Wheels:** Void of defects that would affect safe operation. Wheel bearings should be properly adjusted ball or roller type. (no split race bearings). Wheel balancing weights shall be securely fastened.
- f. **Axle Nuts:** Cotter pinned or safety wired both front and rear.
- g. **Brakes:** Should be foot operated with proper operation and stopping capability suitable for the anticipated performance of the class. Scrubber brakes will be allowed only on Historic Class machines if they were original equipment. Single rear wheel brake should be allowed on Historic machines that were so equipped. Brake linkage must be cotter pinned or safety wired. Any locking type nuts on the brake mechanism which are subject to heat should not be of the plastic insert type. All hydraulic connections must be tight and free of leaks. Vintage Karts using brake calipers of modern design should have a modern design brake disc.
- h. **Throttle:** Karts should be equipped with a foot operated throttle with a spring of suitable strength to return the pedal. The carburetor should have its own return spring that will close the throttle in the event the throttle linkage becomes disconnected.
- i. **Fuel Tanks:** Securely fastened and may be front or rear mounted. Historic class karts may have engine mounted tanks. No pressurized tanks are permitted. No portion of the fuel tank should protrude above the frame causing it to be unprotected in the event of a rollover.
- j. **Chain oilers:** Should not be allowed except for enduros.
- k. **Clutches:** Should not be required. Wet clutches should be permitted only if they do not leak.

Changes are highlighted in yellow.

- l. **Guards:** All chain, belt or gear drives should have a suitable guard to prevent injury in the event of a chain or drive belt failure. It should not be required that the entire drive be enclosed. Any axle mounted sprockets that are not in use must be removed or enclosed.
- m. **Front Suspension and Steering:** Steering shaft should be a minimum of 5/8" cold rolled steel. Steering wheel should be attached by spline or tapered and keyed hub. The hub should not be welded to the steering shaft or secured by a bolt (in shear) passing through the shaft. (Variations and early original equipment permitted). Steering rod ends must be of universal swivel type joints with jam nuts. Linkage bolts must be a minimum of 1/4" grade 5. (Some very early karts had 3/16" rod end bolts: They should be replaced with Grade 8 and inspected often for signs of failure.) All steering assembly bolts, including tie rod ends, spindles and linkage, must be cotter pinned or safety wired. Steering wheels must be cotter pinned or safety wired/lock nutted. Steering must not pass over center, even when reasonable force is exerted. (Karts that do not meet these guidelines should be allowed in static displays only.)
- n. **Frame:** Structurally sound with no defective welds. Minimum wheel tread 28 inches. Seat back and floor pan shall have no voids large enough to allow any part of the driver's body to pass through. Front and/or rear bumpers are not required, but if installed, they shall be solidly attached. All parts and structures of the kart must be suitably attached so as to prevent them from leaving the kart during operation, thereby constituting a hazard.
- o. **Driver's Compartment:** All parts of the driver should be limited to the confines of the width and length of the kart. The feet should not extend beyond the bumper when the pedals are fully depressed. The seating must provide lateral support of the driver. (Some early vintage karts did not have side support, use single engine only). Seat belts are not permitted (required for FKE). (Karts that do not meet these guidelines should be allowed in static displays only.)

10. Event Shows

See the VKA Kart Show Guide for all event show criteria.

11. Demonstration (Tier I)

Tier I Events are flagged and scored.

Motocross or compatible Scoring Guideline

The event should consist of three Heats of equal value. Starting positions may be determined by one of the following methods. All novice and rookie drivers should have an 'X' on the back of the helmet.

In order of Registration

Starting position will be assigned at registration – Earliest entry will start with the pole position. Reverse the order for the Second Heat and High points to the front for the third Heat. All X drivers will start in the back for all Heats.

Changes are highlighted in yellow.

Pea Pick System

Heat One- Karts will be grid in descending pea pick number. Novice drivers will start at the back of the grid.

Heat Two- Grid will be completely inverted from first Heat. Novice drivers remain at the back of the grid.

Heat Three- (main) Total Motocross (or compatible) scoring of the 1st and 2nd Heats will determine the starting position for the main. Novice drivers will remain at the back of the grid.

Qualifying System

Heat One- Karts will grid with fastest time to the front. Novice drivers will remain at the back of the grid.

Heat Two- Karts will grid inverted from their qualifying positions. Novice drivers will remain in the back.

Heat Three- (main) Scoring for the 1st and 2nd Heats will determine the starting position for the main event. Novice drivers will remain in the back.

Heat Scoring (Motocross scoring)

	Points	Position	Points	Position	Points
Position					
1 st	400	6 th	95	11 th	22
2 nd	300	7 th	71	12 th	17
3 rd	225	8 th	53	13 th	13
4 th	169	9 th	40	14 th	9
5 th	127	10 th	30	15 th -20 th	1

In the event of a tie, the winner should be determined by the fastest time, if times are not available, then the winner of the third Heat shall prevail.

In the event of a tie with less than three Heats, the winner should be determined by the fastest time, if times are not available, then the winner of the last Heat shall prevail.

All DNF will start ahead of DNS.

Participant must take the Green Flag to be eligible for points.

12. Demonstration (Tier II)

Tier II Events are non-flagged and not scored.

Tier II event is meant to be: no formal flagged Heats, scoring or awards. Tier II is for practice, testing, kart/motor shakedown and karter get together. If some karters wish to form their own class and have a friendly Heat, that would be the promoter's option.

Changes are highlighted in yellow.

Amendments to VKA Guidelines

◆ *In April 2010 THE VKA BOARD MADE THE FOLLOWING AMENDMENT TO THE VKA GUIDELINES:*

- Change the timeline to include all manufactured karts through 1979.
- All single sidewinder karts prior to 1980 must retain a 1” Axle
- All dual sidewinders may run an axle up to 1¼ inch diameter
- Add an option class for karts produced from 1980-1985 with 100cc engines
- Admit 100cc Yamaha engines to the sidewinder foreign classes -
- Adopt the Motocross Scoring System for all demonstrations.

◆ *In JANUARY 2011 THE VKA BOARD MADE THE FOLLOWING AMENDMENT TO THE VKA GUIDELINES:*

In 2012, Rear Engine Karts will no longer be permitted to Run Modern Style Tires, Traditional Style Tires will be mandatory for VKA events. A list of acceptable Vintage Tires is available on page 8.

◆ *On February 13, .2011 the VKA Board approved the updates to the VKA Guidelines and Approval of the Mac 49/Saw Class*

◆ *On October 9, 2011 the VKA Board approved the updates to the VKA Guidelines. Class restructure, Eligible engines and Karts*

◆ *On December 9, 2012 the VKA Board approved the updates to the VKA Guidelines. Class restructure, Eligible engines and Karts – Addition of the Promoters option class for Stock Appearing*

◆ *On November 10, 2013 the VKA Board approved the updates to the VKA Guidelines. Redefined third bearing support and clutch guard; redefined fuel statement (added propylene oxide); added “Women” to “Junior;” redefined Sportsman Rear/Sidewinder and Stock Appearing to separate Sidewinder and Rear karts; clarified Mac 49/Saw to eliminate large block/stroked engines from the Class; turned “Stock Appearing” into “Sportsman Sidewinder” and expanded carb use; added “Yamaha Piston Port” Class.*

◆ *On November 16, 2014, the VKA Board approved the updates to the VKA Guidelines. Tier I & II events were defined; the age for Juniors was lowered to 10; common clutches were identified; Class 2, Junior/Women was re-defined; the use of “vintage style” clutches was included; tire durometer minimums were re-defined; the age of Dual Sidewinders was defined; clarifications to Yamaha Piston Port Class were made; and engine guidelines were clarified.*

◆ *On Jan 10, 2016, the VKA Board approved the updates to the VKA Guidelines. These changes attempted to make clear that VKA is not a sanctioning organization and these Guidelines are intended to allow promoters to have a consistent set of standards around which they can hold a vintage karting event that will simplify a vintage karter’s preparation for vintage karting events across the country. Changes were also made to emphasize the need for current, full-face Snell Helmet certifications, safe driving during the drivers meeting (and on the track) and the use of*

Changes are highlighted in yellow.

small aftermarket intakes in certain classes. Two additional tires were listed under Acceptable Tires for Sidewinder Karts. A new option class for 2015 was introduced for straight axle sidewinders and 3rd bearing supports or clutch guard for oil clutches on rear engine karts was added.

◆ *On Nov. 13, 2016, the VKA Board approved the updates to the VKA Guidelines. These changes reinforced the need for current Snell rated helmets (2010 or later), clarified the acceptable age/date of vintage karts to 1987, expanded the Junior class to include 100cc engines and certain Yamaha engines and carburetors, expanded the Dual Rear class to include a sub-class of B-Open, limited maximum kart width, limited wheel diameter, limited Over-60 to fan-cooled engines, created a Yamaha Limited class, expanded Class 15, SW Sportsman to include a sub-class for West Bend (US820) engines.*

VKA Disclaimer

The VKA assumes no responsibility for the enforcement or compliance of these *Guidelines*. It is entirely the responsibility of the track owner, event organizer and event director to determine what guidelines are acceptable for their individual event. Event organizers may publish these guidelines under their own promotional materials for their event. Utilization of the VKA name, logo, or endorsement without express permission of the VKA will not be permitted. VKA assumes no responsibility for any claims as a result of any event incidences, accidents, crashes, injuries or deaths.